



QCW Specifications

Band Designation	Frequency Range, GHz	Internal Diameter, inch	Band Designation	Frequency Range, GHz	Internal Diameter, inch
Ku-1	12.4-14.6	0.66	E-0	58-68	0.141
Ku-2	14.6-17.5	0.55	E-1	68-77	0.125
K-1	17.5-20.5	0.47	E-2	77-87	0.11
K-2	20.5-24.5	0.396	E-3	87-100	0.094
K-3	24.5-26.5	0.328	W-0	77-87	0.11
Ka-0	26-28.5	0.328	W-1	87-100	0.094
Ka-1	28.5-33	0.281	W-2	100-112	0.082
Ka-2	33-38.5	0.25	F-0	87-100	0.094
Ka-3	38.5-43	0.219	F-1	100-112	0.082
Q-0	33-38.5	0.25	F-2	112-125	0.075
Q-1	38.5-43	0.219	F-3	125-140	0.067
Q-2	43-50	0.188	D-0	100-112	0.082
U-0	38.5-43	0.219	D-1	112-125	0.075
U-1	43-50	0.188	D-2	125-140	0.067
U-2	50-58	0.165	D-3	140-160	0.059
V-0	50-58	0.165	G-0	125-140	0.067
V-1	58-68	0.141	G-1	140-220	0.059
V-2	68-77	0.125			

Custom Products available. Contact us at sales@quinstar.com or submit an RFQ.